



# SUNSHIELD ENTERPRISE

Steven Sim

Phone: 63466325

Email: [sales@watercooler.com.sg](mailto:sales@watercooler.com.sg)

<http://www.watercooler.com.sg>

D19A

Point of use  
Coolers



OFF WHITE



BLACK





# SUNSHIELD ENTERPRISE

Steven Sim

Phone: 63466325

Email: [sales@watercooler.com.sg](mailto:sales@watercooler.com.sg)

<http://www.watercooler.com.sg>

## Clover SD19 Features

### ■ Details

<b>CABINET</b>	High glossy cabinet, Front and top: ABS plastic, Side: High polymer polyester coated steel panel or Pre-coated metal. Superior resistance to UV light.
<b>COLOR</b>	Off White, Black
<b>FAUCETS</b>	Durable structure. Self closing type. Easy to operate. Child-safe hot water faucet. Cup push type.
<b>DRIP TRAY</b>	Concealed, liftout design, high impact, durable ABS. Removable, anti-splash grid diverts drip water into receptacle.
<b>FLOW CONTROL</b>	Leakage-preventive dual floats valve system, in case of malfunction of the primary valve, the secondary valve stops the water inflow to minimize the damage on the property.
<b>FILTER COMPARTMENT</b>	pace for water filtration systems on the back of the front panel.
<b>COLD WATER TANK</b>	Hygienic stainless steel. External refrigerant evaporator. Mechanically wrapped around tank. Removable insulation in molded expanded bead polystyrene contaminant-resistant design. Adjustable cold water thermostat.
<b>COLD WATER THERMOSTAT</b>	Temperature is controlled to 35.6°F~53.6°F(2°C~12°C) by adjustable thermostat, easily accessible on back.
<b>REFRIGERATION UNIT</b>	Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector. No lubricant needed. Refrigerant is controlled by accurately calibrated capillary tube.
<b>HOT WATER TANK</b>	Hygienic stainless steel. Highly efficient internal heating element. Non-adjustable thermostat with manual reset safety limiter. Convenient hot water ON/OFF switch. Fire proof insulation.
<b>HOT WATER THERMOSTAT</b>	Water temperature is controlled to nearly 185°F(85°) automatically, ON/OFF switch is easily accessible on back.
<b>ELECTRICAL</b>	220V ~ 240V(±10%) 50/60Hz, 100V ~ 127V(±10%) 50/60Hz provided with power cord. Units of other power supplies available upon special order.
<b>QUALITY</b>	Our models covered by these specifications are manufactured to comply with the standards of overseas quality program.
<b>WARRANTY</b>	One year on the sealed refrigeration system and most component Part.
<b>PACKING</b>	Export standard carton packing.
<b>REFRIGERANT TYPE</b>	R134a

Clover



# SUNSHIELD ENTERPRISE

Steven Sim

Phone: 63466325

Email: [sales@watercooler.com.sg](mailto:sales@watercooler.com.sg)

<http://www.watercooler.com.sg>

## Clover SD19 Specifications

### ■ Tech Info

<b>Cold Water</b>	Capacity(L)	3.2
	Tank Volume(L)	3.32
	Temp. Range(°C)	2 ~ 8
	Compressor Type	Single phasereciprocating
	Refrigerant Charge(g)	31
<b>Hot Water (Type A Only)</b>	Capacity(L)	6.5
	Tank Volume(L)	1.8
	Temp. Range(°C)	82 ~ 92
	Heater Type	Sheathed heater
<b>Dimensions W X D X H (mm)</b>	Net	272 x 313 x 945
	Shipping	285 x 340 x 980
<b>Weight (kg)</b>	Net	15.2
	Shipping	17.2
<b>Certificates</b>		CE/CB

▪ Type A : Cold & Hot Model

▪ Capacity: The above rates tested in ambient temperature 90°F(32°C) with same water inlet temperature.

(POUs tested with water inlet temperature 26.5°C)

Specification of products are subject to change without notice.