



SUNSHIELD ENTERPRISE

Steven Sim

Phone: 63466325

Email: sales@watercooler.com.sg

<http://www.watercooler.com.sg>

SD19A/
Point of use
Coolers



OFF WHITE



BLACK





SUNSHIELD ENTERPRISE

Steven Sim

Phone: 63466325

Email: sales@watercooler.com.sg

<http://www.watercooler.com.sg>

Clover SD19 Features

CABINET	High glossy cabinet, Front and top: ABS plastic, Side: High polymer polyester coated steel panel or Pre-coated metal. Superior resistance to UV light. Removable side panel grill for easy access to internal parts for maintenance. Side handle for carrying.
COLOR	Off White, Black
FAUCETS	Durable structure. Self closing type. Easy to operate. Child-safe hot water faucet. Cup push type.
DRIP TRAY	Concealed, liftout design, high impact, durable ABS. Removable, anti-splash grid divets drip water into receptacle.
FLOW CONTROL	Leakage-preventive dual floats valve system, in case of malfunction of the primary valve, the secondary valve stops the water inflow to minimize the damage on the property.
FILTER COMPARTMENT	Space for water filters inside of the system
COLD WATER TANK	Hygienic stainless steel. External refrigerant evaporator. Mechanically wrapped around tank. Removable insulation in molded expanded bead polystyrene contaminant-resistant design. Adjustable cold water thermostat.
COLD WATER THERMOSTAT	Temperature is controlled to 35.6°F~53.6°F(2°C~12°C) by adjustable thermostat, easily accessible on back.
REFRIGERATION UNIT	Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector. No lubricant needed. Refrigerant is controlled by accurately calibrated capillary tube.
HOT WATERTANK	Energy saving construction. Hygienic stainless steel. Highly efficient internal heating element. Non-adjustable thermostat with manual reset safety limiter. Convenient hot water ON/OFF switch. Fire proof insulation.
HOT WATER THERMOSTAT	THERMOSTAT Water temperature is controlled to nearly 185°F(85°) automatically, ON/OFF switch is easily accessible on back.
ELECTRICAL	220V ~ 240V(±10%) 50/60Hz, 100V ~ 127V(±10%) 50/60Hz provided with power cord. Units of other power supplies available upon special order.
QUALITY	Our models covered by these specifications are manufactured to comply with the standards of overseas quality program.
WARRANTY	One year on the sealed refrigeration system and most component Part.
REFRIGERANT TYPE	R134a

Clover



SUNSHIELD ENTERPRISE

Steven Sim

Phone: 63466325

Email: sales@watercooler.com.sg

<http://www.watercooler.com.sg>

Clover SD19 Specifications

■ Tech Info

Cold Water	Capacity(L)	2.3
	Tank Volume(L)	3.32
	Temp. Range(°C)	2 ~ 8
	Compressor Type	Single phasereciprocating
	Refrigerant Charge(g)	30
Hot Water (Type A Only)	Capacity(L)	6.5
	Tank Volume(L)	1.5
	Temp. Range(°C)	82 ~ 92
	Heater Type	Sheathed heater
Dimensions W X D X H (mm)	Net	272 x 420 x 438
	Shipping	285 x 502 x 516
Weight (kg)	Net	14.3
	Shipping	16.4
Certificates		UL,ENERGY STAR,CE/CB

- Type A : Cold & Hot Model

- Capacity: The above rates tested in ambient temperature 90°F(32°C) with same water inlet temperature.
(POUs tested with water inlet temperature 26.5°C)
- Specification of products are subject to change without notice.